

# EZZTANK DISPLAY UNIT



Technical  
Specification  
COMTUSTEC INDIA (P) LTD

## Overview

EZZTANK Display unit is plug and play device which actively displays the water level data from EZZTANK sensor unit through RF connectivity and also posts seamless data and various alerts of water level to the server.

## General

Peak Current 192 mA

Sleep Current 124 mA

## Transmitter Connectivity

Connectivity RF Connectivity

Frequency 867MHz

Reception Interval Active always

**RF Range: Open Air 30 Meters**

Antenna Spiral antenna 867MHz

## Cloud Connectivity

Connectivity Wi-Fi

Operating frequency 2412MHz to 2484MHz

Transmission Interval 5s /30s

Temperature	-20° to 65°C
Types of Alerts	<ol style="list-style-type: none"> <li>1) Tank empty</li> <li>2) Tank full</li> <li>3) Clean tank</li> <li>4) Communication error</li> <li>3) Transmitter - Low battery</li> </ol>
LED Indication	Yes
Buzzer Indication	Yes
Display	
Display Model	TFT Display
Display Size	2.8 Inch
Mechanical	
Case Colour	White/Black (As per requirement)
Size	60mm x 100mm x 65mm
Net Weight	124 grams
Warranty	
Warranty Summary	1 Year (*Only Manufacturing Defects)