

EZZTANK DISPLAY UNIT



Technical
Specification

COMTUSTEC INDIA (P) LTD

Overview

EZZTANK Display gateway unit is plug and play device which actively displays the water level data from EZZTANK sensor unit through RF connectivity and show live water level data and alert of the water level also in online mode seamless data to the server.

General

Power	220VAC / 50 HZ
Peak Current	200 mA
Sleep Current	124 mA

Transmitter Connectivity

Connectivity	RF Connectivity
Frequency	867MHz
Reception Interval	Active always
RF Range:	Open Air (800 Meters)
Antenna	Spiral antenna 867MHz

Cloud Connectivity

Connectivity	Wi-Fi
Operating frequency	2412MHz to 2484MHz
Transmission Interval	5s /30s
Temperature	-20° to 65°C
Types of Alerts	<ol style="list-style-type: none"> 1) Tank empty 2) Tank full 3) Clean tank 4) Communication error 3) Sensor - Low battery

LED Indication Yes

Buzzer Indication Yes

Display

Display Model TFT Display

Display Size 2.8 Inch

Backlight Brightness Adjustable

Mechanical

Case Colour White/Black (As per requirement)

Size 60mm x 100mm x 65mm

Net Weight 124 grams

Warranty

Warranty Summary 1 Year (*Only Manufacturing Defects)